

|: 210-719

Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft

<https://www.wago.com/210-719>



#### Technical data

|                       |                |
|-----------------------|----------------|
| Main product function | Operating tool |
| Number of spacings    | 1 -times       |

#### Physical data


|        |        |
|--------|--------|
| Length | 175 mm |
|--------|--------|

#### Material data


|           |      |
|-----------|------|
| Fire load | 0 MJ |
| Weight    | 26 g |

#### Commercial data

|                                     |                                |
|-------------------------------------|--------------------------------|
| Product Group                       | 2 (Terminal Block Accessories) |
| eCl@ss 10.0                         | 21-04-04-07                    |
| eCl@ss 9.0                          | 21-04-04-07                    |
| ETIM 8.0                            | EC000158                       |
| ETIM 7.0                            | EC000158                       |
| PU (SPU)                            | 50 (1) Stück                   |
| Packaging type                      | Bag                            |
| Country of origin VKOrg Germany     | DE                             |
| GTIN                                | 4045454937386                  |
| Customs tariff number VKOrg Germany | 82055980000                    |

**Installation notes**

Inserting conductor via (2.5 x 0.4) mm screwdriver – CAGE CLAMP® actuation perpendicular to conductor entry.



The blade dimensions of the above-listed operating tools with a partially insulated shaft are ideal for easy operation of front-entry terminal blocks.